



TTP

Single-Speed Torque Gun

FEATURES

- Accurate torque with low noise and low vibration
- Maximum torque requires only 90 PSI
- Extensions available for job-specific applications
- Made from lightweight, high-strength materials
- Precision gearing produces constant calibrated power
- Highest power-to-weight ratio of any comparable product
- Splined reaction area allows for the use of custom reaction fixture

SPECIFICATIONS



LEGEND: H = HEIGHT L = LENGTH R = RADIUS W = WIDTH

Model		H	W	L	R	Drive	Weight	Torque	
								MIN.	MAX.
TTP - .25	in.	7.06	2.72	7.15	1.25	0.75	7.20 lbs.	85 ft.-lbs.	250 ft.-lbs.
	mm	179	69	182	32	19	3.27 kg	115.25 Nm	338.95 Nm
TTP - .5	in.	7.32	2.74	8.07	1.25	.75	7.20 lbs.	175 ft.-lbs.	500 ft.-lbs.
	mm	186	70	205	32	19	3.27 kg	237.27 Nm	677.91 Nm
TTP - 1	in.	7.06	2.72	8.82	1.25	.75	8.80 lbs.	200 ft.-lbs.	1,250 ft.-lbs.
	mm	179	69	224	32	19	3.99 kg	271.16 Nm	1,694.77 Nm
TTP - 2	in.	7.94	3.53	10.46	3.25	1	14.50 lbs.	521 ft.-lbs.	2,190 ft.-lbs.
	mm	202	90	266	83	25	6.58 kg	706.38 Nm	2,969.24 Nm
TTP - 3	in.	7.94	3.53	11.11	1.31	1	15.75 lbs.	856 ft.-lbs.	3,180 ft.-lbs.
	mm	202	90	282	33	25	7.06 kg	1,160.58 Nm	4,311.50 Nm
TTP - 5	in.	7.93	3.70	12.24	1.81	1.5	20.05 lbs.	1,200 ft.-lbs.	5,200 ft.-lbs.
	mm	201	94	311	46	38	9.10 kg	1,626.98 Nm	7,050.25 Nm
TTP - 8	in.	8.03	3.69	13.00	1.81	1.5	26.50 lbs.	1,775 ft.-lbs.	8,035 ft.-lbs.
	mm	204	94	330	46	38	12.02 kg	2,406.58 Nm	10,894.00 Nm

NOTE:

All tools and pumps are subject to a 13-months free repair/replacement guaranty in the event of failure. Data subject to change without notice.